


*Latte*

## SPECIFICATIONS

Suggested Use	Gravel, Road, Adventure
Sizes	Small, Medium, Large
Total Weight	42.3 lbs. (L size)
Frame	Yamaha Hydroformed Aluminum. Internal shift/brake hose routing (hose-clamp guides under top tube for external dropper post configurations)
Fork	One-Piece Aluminum. 12x100mm Thru-Axle. Fender compatible. Internal brake hose routing
Battery	Yamaha 500Wh 36V Lithium Ion
Drive Unit	Yamaha PWSeries SE 3-bolt Mount
Crankarm	Square Taper Spindle. S=165mm, M,L=170mm
Chainring	SRAM APEX 1 50t
Shifter	SRAM APEX 1 HRD
Rear Derailleur	SRAM APEX 1
Brakes/Rotors	SRAM APEX Hydraulic. 160mm Center Lock Rotors
Cassette	SRAM PG-1130. 11-42t. 11-Speed
Chain	KMC X11e
Hubs	Front: 12x100mm TA Rear: 12x142mm TA with integrated speed sensor
Rims	32-Hole Dual Channel Welded Pin w/ Eyeleted Spoke
Holes	24.5mm External Width, 19mm Internal Width
Spokes	SUS304 w/ brass nipple
Tires/Tubes	Maxxis Speed Terraine 700 x 33c TR EXO
Headset	Integrated bearing with 30mm of spacers
Stem	4-bolt, 31.8 clamp dia. S=50mm, M,L=70mm
Handlebar	Flare Drop. 31.8 dia. S=40cm c-c "width at hood", 51cm c-c "width at drop" M,L=44cm c-c "width at hood", 51cm c-c "width at drop"
Grips/Tape	Padded Cork Tape
Seatpost	Alloy 30.9, 2-Bolt Tilt Adjustable. S=260mm, M=315mm, L=350mm
Seatpost Collar	Alloy 2-bolt 35.0mm diameter
Saddle	Yamaha Off-Road Cro-Mo Rail

## FEATURES

Wheels and Tires Ready for Off-Road  
 Wide-flare Gravel Handlebar for Added Control  
 Ergonomic Control Switch  
 Triple Sensor System with Rear Hub Speed Sensor  
 Rated Power: 250W (Nominal), 500W (Max.)  
 Max. Torque: 70Nm  
 Max. Cadence Support: 110rpm  
 Max. Speed Support: 20mph  
 4 Power Assist Modes: ECO+, ECO, STANDARD, HIGH  
 Internal Cable/Housing Routing  
 Dropper Post Compatible  
 Fender and Rear Rack Compatible

**Accessories** Yamaha Keys  
 Yamaha Battery Charger  
 LED Headlamp  
 Bell  
 Handlebar Accessory Mount

**Warranty** 3-Year on Frame, Drive Unit, Battery\*  
 Component manufacturer's warranty by Yamaha

## FRAME GEOMETRY

	S	M	L
Top Tube (Effective)	530	550	580
Reach	373	392	405
Stack	548	555	573
Standover Height	725	751	797
Head Tube Length	130	135	150
Head Tube Angle	71	72	72.5
Seat Tube Length	430	463	530
Seat Tube Angle	74	72	73
Bottom Bracket Drop	61	61	61
Wheelbase	1039	1051	1064
Rear Center	455	455	455