

MSRP: \$4099



Blue Steel

SPECIFICATIONS

Suggested Use	Gravel, Road, Adventure
Sizes	Small, Medium, Large
Total Weight	xx.x lbs. (L size)
Frame	Yamaha Hydroformed Aluminum. Integrated battery. Water bottle boss. Tapered Headtube. Internal shift/brake hose routing
Fork	One-Piece Aluminum. 12x100mm Thru-Axle. Fender and rack compatible. Internal brake hose routing
Battery	Yamaha 500Wh 36V Lithium Ion
Drive Unit	Yamaha PWSeries ST 3-bolt Mount
Crankarm	Square Taper Spindle Length S-165mm, M and L - 170mm
Chainring	Shimano GRX 44t
Shifter	Shimano GRX 11-speed RX600
Rear Derailleur	Shimano GRX
Brakes	Shimano GRX RX600-rear, RX400-front
Rotors	180mm Centerlock
Cassette	Shimano CS-M7000 11-42t 11-Speed
Chain	KMC e11 Turbo EPT
Hubs	Front: 12x100mm TA Rear: 12x142mm TA with integrated speed sensor
Rims	32-Hole Dual Channel Welded Pin w/ Eyeleted Spoke
Holes	24.5mm External Width, 19mm Internal Width
Spokes	SUS304 w/ brass nipple
Tires/Tubes	Maxxis Rambler 700 x 45c TR EXO 120tpi
Headset	Integrated bearing with 30mm of spacers
Stem	31.8 clamp dia. 6 deg rise S-80mm, M-90mm, L-100mm
Handlebar	Flare Drop. 31.8 dia. 44cm c-c "width at hood", 51cm c-c "width at drop"
Grips/Tape	Padded Cork Tape
Seatpost	30.9 diam. Dropper post Dropper Travel S-40mm, M and L-60mm
Seatpost Collar	Alloy 2-bolt 35.0mm diameter 2-bolt
Saddle	Yamaha Off-Road Cro-Mo Rail

FEATURES

- Gravel specific ergonomics and geometry
- Wheels and tires ready for off-road
- Wide-flare gravel handlebar
- Dropper post
- Fender and rear rack compatible
- Quad Sensor System with rear hub speed sensor
- Rated power: 250W (Nominal), 500W (Max.)
- Max. torque: 70Nm
- Max. cadence support: xxxrpm
- Max. speed support: 28mph
- 5 Assist modes: AUTO, ECO+, ECO, STANDARD, HIGH
- Accessories** Yamaha keys
Yamaha battery charger
Bell
- Warranty** 3-Year on Frame, Drive Unit, Battery*

FRAME GEOMETRY

	SMALL	MEDIUM	LARGE
TOP TUBE (effective)	535	565	595
REACH LENGTH	368	382	402
STACK HEIGHT	595	607	617
STANDOVER HEIGHT	781	818	852
HEADTUBE LENGTH	121	131	142
HEADTUBE ANGLE	71.1	71.8	71.9
SEAT TUBE ANGLE	74.4	73.3	72.6
SEAT TUBE LENGTH	429	490	551
SEAT POST LENGTH	340	395	440
DROPPER POST TRAVEL	75	100	125
STEM LENGTH	70	70	70
BB DROP	73	73	73
WHEELBASE	1057	1068	1090
REAR CENTER	464	464	464
CRANKARM LENGTH	172.5	172.5	172.5
HANDLEBAR WIDTH	44	44	44

*Full Details on Warranty Sheet